



HIGHLIGHTS

Commercial Grade

Ruggedized engineering to support the harsh environments of any fleet application.

High Quality

Built with premium components to ensure excellent picture quality in any conditions.

Performance Backed

All add-on cameras come with a 2-year warranty against any manufacturer's defect.

+

- Three Mounting Options (0°, 15°, 25°)
- Sony 1/3.2"
- 2.8mm Lens
- 720P AHD
- Diagonal Field of View 105°
- Digital Noise Reduction (DNR)
- DC 12V
- Infrared LEDs for Night-time Recording
- Simple and Secure Angle Control

SVA034-AWP Technical Specifications



Synchronization	Internal	TV Mode	PAL
Electronic Shutter		Auto	
Infrared Spectrum		850nm	
Power Supply		12V DC±10%	
Audio	Available	Power Consumption	170mA (Max)
ICR	Available	Operating Temperature	-30° C ~ +70 ° C
Dimensions (ø X H)		77 x 60.3 mm	
Net Weight		200 g	
Weatherproof/ Water Proof	IP66	Mirror	OFF
Image Sensor		Sony 1/3.2"	
Noise Reduction		3D	
AGC		Auto	
Picture Elements		1280 (H) x 960 (V)	
Video Output		1 Vp-p, 75Ω,AHD	
Scanning System		Progressive scan RGB CMOS	
BLC		Auto	
Dynamic range		120 dB	
Infrared LED		10 LEDs (ø3.0)	
Lens		F2.8mm Megapixel	
Sensitivity		0 Lux (IR LED On)	
S/N Ratio		More than 44dB (AGC Off)	
Compatible Hardware Platforms		CP4S, CRXS	
Required Accessories		CP4S: SVA-05-EXT-B CRXS: SVA-05-EXT-A	
Warranty		2-year standard	