



## HIGHLIGHTS

### Commercial Grade

Ruggedized engineering to support the harsh environments of any fleet application.

### High Quality

Built with premium components to ensure excellent picture quality in any conditions.

### Performance Backed

All add-on cameras come with a 2-year warranty against any manufacturer's defect.

+

- 1.3MP SONY CMOS SENSOR
- Wide View 120° (f2.9mm lens)
- Wide Dynamic Range (WDR)
- Digital Noise Reduction (DNR)
- DC 12V
- Infrared LEDs for Night-time Recording
- Easy Windshield Installation with 3M Adhesive
- Simple and Secure Angle Control

# SVA035-AWP Technical Specifications



|                                       |  |                |     |
|---------------------------------------|--|----------------|-----|
| <b>Synchronization</b>                | Internal                                 | <b>TV Mode</b> | PAL |
| <b>Power Source</b>                   | DC 9V – 40V                              |                |     |
| <b>Picture Elements</b>               | 1280 (H) x 720 (V)                       |                |     |
| <b>Power Consumption</b>              | DC12V, 160mA(LED ON)/100mA(LED OFF)      |                |     |
| <b>Dimensions</b>                     | 60.8mm(W) x 69.6mm(D) x 71.6mm(H)        |                |     |
| <b>Language</b>                       | English                                  |                |     |
| <b>Housing Color</b>                  | Black                                    | <b>Mirror</b>  | ON  |
| <b>Image Device</b>                   | 1.3 Mega-Pixel Sony CMOS Sensor          |                |     |
| <b>AGC</b>                            | OFF / 1 ~ 15                             |                |     |
| <b>Weatherproof/Waterproof Rating</b> | IP69K                                    |                |     |
| <b>Video Output</b>                   | AHD 1.0 ( 720p@30 / 25fps)               |                |     |
| <b>Scanning Mode</b>                  | Progressive                              |                |     |
| <b>BLC</b>                            | Off / Low / Middle / High                |                |     |
| <b>Operating Temperature</b>          | -20c-+60°C                               |                |     |
| <b>Infrared LED</b>                   | 12 IR LEDs                               |                |     |
| <b>Lens</b>                           | f2.9mm lens                              |                |     |
| <b>Sensitivity</b>                    | 0.1Lux (F1.2,@50IRE)                     |                |     |
| <b>S/N Ratio</b>                      | More than 50dB AGC OFF                   |                |     |
| <b>Compatible Hardware Platforms</b>  | CP4S, CRXS                               |                |     |
| <b>Required Accessories</b>           | CP4S: SVA-05-EXT-B<br>CRXS: SVA-05-EXT-A |                |     |
| <b>Warranty</b>                       | 2-year standard                          |                |     |