



ACCESSORY

SV7QLCD-T

In-Cab Monitor



HIGHLIGHTS

Commercial Grade

Ruggedized engineering to support the harsh environments of any fleet application.

High Quality

Built with premium components to ensure excellent picture quality in any conditions.

Performance Backed

All add-on cameras come with a 2-year warranty against any manufacturer's defect.



- Ruggedized design for commercial fleet use
- Supports a single input channel
- Vehicle triggers automatically enhance visibility for drivers
- Compatible with DVR hardware platforms
- Flexible mounting options

SV7QLCD-T Technical Specifications



System Signal	NTSC / PAL
LCD Panel	7" Thin Film Transistor (TFT)
Image	16 : 9 Color
Brightness	300 cd/m2
Video / Audio In	4 pin aviator connector, 1 channel
Input Triggers	1
View Angle	Left, right and down - 70° / Up - 50°
Total Pixel	800 x 480 Resolution
Power Range	DC 9~32 V
Power Protection	High/low and short circuit
Bracket	Metal U type
Sun Shade	Detachable
Language	English / Chinese / Espanol / Russian / Deutsch / Portuguese / French / Japanese
Dimensions Without Sunshade	178mm (W) x 120mm (D) x 23.5mm (H) 7 " (W) x 4.72" (D) x .925" (H)
Compatible Hardware Platforms	CP4S, CRXS
Warranty	2-year standard



ACCESSORY

SV7QLCD-T4

In-Cab Monitor



HIGHLIGHTS

Commercial Grade

Ruggedized engineering to support the harsh environments of any fleet application.

High Quality

Built with premium components to ensure excellent picture quality in any conditions.

Performance Backed

All add-on cameras come with a 2-year warranty against any manufacturer's defect.



- Ruggedized design for commercial fleet use
- Supports up to 4 separate inputs
- Vehicle triggers automatically enhance visibility for drivers
- Compatible with DVR hardware platforms
- Flexible mounting options

SV7QLCD-T4 Technical Specifications



System Signal	NTSC
LCD Panel	7" Thin Film Transistor (TFT)
Image	16 : 9 Color
Brightness	300 cd/m2
Video / Audio In	4 pin aviator connector, 4 channels
Input Triggers	4
View Angle	Left, right and down - 70° / Up - 50°
Total Pixel	800 x 480 Resolution
Power Range	DC 9~32 V
Power Protection	High/low and short circuit
Bracket	Metal U type
Sun Shade	Detachable
Language	English / Chinese / Espanol / Russian / Deutsch / Portuguese / French / Japanese
Dimensions Without Sunshade	178mm (W) x 120mm (D) x 23.5mm (H) 7 " (W) x 4.72" (D) x .925" (H)
Compatible Hardware Platforms	CP4S, CRXS
Warranty	2-year standard