



HIGHLIGHTS

Commercial Grade

Ruggedized engineering to support the harsh environments of any fleet application.

High Quality

Built with premium components to ensure excellent picture quality in any conditions.

Performance Backed

All add-on cameras come with a 2-year warranty against any manufacturer's defect.

+

- Three Mounting Options (0°, 15°, 25°)
- 1/3" CMOS AR0130
- 2.8mm Lens
- 720P AHD
- Diagonal Field of View 105°
- Digital Noise Reduction (DNR)
- DC 5~12V 12
- Infrared LEDs for Night-time Recording
- Simple and Secure Angle Control

SVA034-A Technical Specifications



Synchronization	Internal	TV Mode	NTSC
Electronic Shutter	Auto		
Infrared Spectrum	850nm		
Power Supply	9-18V DC		
Audio	Available	Power Consumption	145mA(Max)
ICR	Available	Operating Temperature	-30° C ~ +70 ° C
Dimensions (Ø X H)	77 x 60.3 mm		
Net Weight	200 g		
Weatherproof/ Water Proof	IP66	Mirror	OFF
Image Sensor	1/3" CMOS AR0130		
Noise Reduction	3D		
AGC	Auto		
Effective Pixels	1280 (H) x 960 (V)		
Video Output	1 Vp-p, 75Ω,AHD (CVBS)		
Scanning Mode	Progressive scan RGB CMOS		
BLC	Auto		
Dynamic range	83.5 dB		
Infrared LED	10 LEDs (Ø3.0)		
Lens	F2.8mm Megapixel		
Sensitivity	0 Lux (IR LED On)		
S/N Ratio	More than 44dB (AGC Off)		
Compatible Hardware Platforms	CP4S, CRXS		
Required Accessories	CP4S: SVA-05-EXT-B CRXS: SVA-05-EXT-A		
Warranty	2-year standard		